

AQTiV COMBI

PRODUCT SHEET

TAP



| | | |
|------------------------|--|------------------------|
| Versions | AQTiV COMBI | AQTiV COMBI H |
| Dimensions (mm) | H: 426, W: 104, D: 344 | H: 550, W: 104, D: 344 |
| Dispensing height (mm) | H: 113 | H: 285 |
| Water | Filtered fresh, still and sparkling water / Unfiltered hot and cold water | |
| AQTiV Technology | Through an innovative system combining a vortex mechanism, 18 micro-jets for optimal water aeration, and annular air protection around the nozzle extremity, the water flows in an accelerated movement, resulting in improved aeration and oxygenation. | |
| Drilling hole (mm) | Ø 35 | |

BE CONNECT

| | |
|-------------------------|--|
| Intelligent filter head | <ul style="list-style-type: none"> Ensures optimal water quality and systems maintenance Controls filter and gaz capacity Checks temperature and ventilation Energy saving system Leak detector with automatic water flow stoppage Linked to a web application to monitor the system |
| Filter | <ul style="list-style-type: none"> Removal of chlorine, organic substances and "off-flavour" components Fine particles and suspended solids filtration Microplastics barrier High reduction of bacteria (99,99%) Keep good local minerals |
| Filter capacity | 6'000L |
| Dimensions (mm) | H: 350, W: 100, D: 215 |

AQTiV COMBI

PRODUCT SHEET

BOX (Depending on the consumption)

| Type | BOX 20 | BOX 30 | BOX 80 |
|---------------------|---------------------------|---------------------------|---------------------------|
| Adapted for | Home | Office | HoReCa |
| Chilling technology | Direct chill | Dry chill | Ice Bank |
| Capacity | 20l/h | 30l/h | 80l/h |
| Recirculation | - | - | Available |
| Dimensions (mm) | H: 440, W: 200, D: 265 | H: 416, W: 320, D: 416 | H: 480, W: 320, D: 500 |
| Product code | | | |
| With AQTiV COMBI | BWS-0047 | BWS-0028 | BWS-0041 |
| With AQTiV COMBI H | BWS-0048 | BWS-0029 | BWS-0042 |

GAS

Dimensions Depends on our local supplier, please contact customer service

Needed for installation

Water inlet

Electrical outlet 230 V

Under counter

Dimensions needed under the counter With BOX 30, BOX 80, our systems can be installed in a standard cabinet of 60 cm x 60 cm

Our system with a BOX 20 is specially designed to also leave place for a 40L trash can under the sink

Do not hesitate to contact our customer service for more information

Under counter elements

